

LX400 Color Label Printer Specifications

Print Method: Inkjet

Print Resolutions: 4800 x 1200 dpi, 1200 x 1200 dpi, 600 x 600 dpi

Ink Cartridge: One Multicolor (CMY) with Process Black

Colors: 16.7 million

Color Matching: Z-Color™ Color Matching Software

Print Width: 0.75" (19mm) to 4" (101.6mm)

Print Length: 0.75" (19mm) to 24" (609.6mm)

Media Width: 1" (25.4mm) to 4.25" (108mm)

Media Types: Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tags

Media Sensing: Moveable see-through sensor for die-cut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock.

Supply Roll: 5" (127mm) maximum diameter on 2" (50.8mm) core. Core has additional restrictions – see manual.

Ink Level Warning: Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)

Indicator Lights: Power, Ink

Controls: Pause, Load/Feed, Unload

Operating Systems: Windows® XP/2000/Vista® or Mac® OS X, 10.2 or higher

Recommended Minimum System:

For PC: Pentium® IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 or USB 1.1

For Mac: 700 Mhz G4 or higher with 512MB RAM, 5GB free hard drive space, USB 2.0 or USB 1.1

Label Design Software: NiceLabel™ SE Primera Edition included. Can also be used with most other popular label design software programs.

Electrical Rating: 12VDC, 5.0A

Power Requirements: 100-240VAC, 50/60 Hz, 60 watts

Certifications: UL, UL-C, CE, FCC Class A

Weight: 7.0 lbs. (3.2 kg)

Dimensions: 10.4"W x 15.5"D x 7.1"H (closed), 17.4" (open)
264mmW x 389mmD x 180mmH (closed), 442mmH (open)

Options: Ink Cartridge, #53376



love barcodes