

## **LX810 Color Label Printer Specifications**

**Print Method:** Inkjet

**Print Resolutions:** 4800 x 1200 dpi, 2400 x 1200 dpi, 600 x 600 dpi

**Print Speeds:** Approximately 2" (51mm) per second for black Approximately 1.5" (38mm) per second for color + black  
Approximately 10" per second feed rate

**Ink Cartridges:** Color (CMY), Black Dye-Based (Kd), Black Pigment-Based (Kp)

**Colors:** 16.7 million

**Color Matching:** Z-Color™ Color Matching Software

**Min. Print Width:** 0.75" (19mm) **Max. Print Width:** 8.25" (210mm)

**Min. Print Length:** 0.75" (19mm) **Max. Print Length:** 24" (609mm)

**Min. Media Width:** 1.5" (38.1mm)

**Media Types:** Roll-fed pressure-sensitive labels, roll-fed tags

**Media Sensing:** Moveable see-through sensor for die-cut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock

**Supply Roll:** 6" (152mm) maximum diameter on 3" (76mm) core

**Ink Level Warning:** Calculates actual number of prints remaining based upon ink usage of graphics being printed

**Indicator Lights:** Power, Pause, Ink

**Controls:** Pause, Feed, Stop/Cancel

**Operating Systems:** Windows XP/2000 and Vista® or Mac OS X, 10.2 or higher

**Data Interface:** USB 2.0

**Recommended Minimum System:**

For PC: Pentium® IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended) For Mac®: 700 Mhz G4 or higher with 512MB RAM, 5GB free hard drive space, USB 2.0 (recommended)

**Label Design:** NiceLabel™ SE Primera Edition included

**Software:** Can also be used with most other popular label design software programs

**Electrical Rating:** 12VDC, 5.0A

**Power Requirements:** 100-240VAC, 50/60 Hz, 60 watts

**Certifications:** UL, UL-C, CE, FCC Class B

**Weight:** 29 lbs. (13.2 Kg)

**Dimensions:** 17"W x 9.1"H x 15.5"D (432mmW x 231mmH x 394mmD)

